

a printer interface which generates printed copy signals corresponding to the digital record, the printed copy signals being effective in printing an image derived from the captured image when coupled to a printer;

a controller which couples said image capture device and said printer interface, said controller having

a first network interface which connects to an area network for bidirectional exchange of digital data; and

a second network interface which connects to a second network for bidirectional exchange of digital data; and

A
1
a control program stored accessibly to and executable on said controller, said control program when executing enabling a user to select delivery of the digital record to a selected one of said printer interface, said first network interface, and said second network interface.

7. Apparatus according to Claim 6 wherein said control program when executing on said controller enables a user to access a remotely stored database of address information.

8. Apparatus according to Claim 6 further comprising:

a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and enabling access to said database of address information stored in said memory.

9. Apparatus according to Claim 6 further comprising
2037
a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and to selectively access one of said

database of address information stored in said memory and a second database of address information stored remotely from said controller and accessible through said first network interface.

10. Apparatus comprising:
- an image capture device which generates a digital record;
 - a printer interface which generates printed copy signals corresponding to the digital record, the printed copy signals being effective in printing an image derived from the captured image when coupled to a printer;
 - a controller which couples said image capture device and said printer interface, said controller having
 - a first network interface which connects to an area network for bidirectional exchange of digital data; and
 - a second network interface which connects to a second network for bidirectional exchange of digital data; and
 - a control program stored accessibly to and executable on said controller, said control program when executing enabling a user to select delivery of the digital record to any selected two of said printer interface, said first network interface, and said second network interface.
11. Apparatus according to Claim 10 wherein said control program when executing on said controller enables a user to access a remotely stored database of address information.
12. Apparatus according to Claim 10 further comprising:
- a memory coupled to and housed with said controller;

said control program when executing on said controller further enabling a user to store a database of address information in said memory and enabling access to said database of address information stored in said memory.

520 7 13. Apparatus according to Claim 10 further comprising
a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and to selectively access one of said database of address information stored in said memory and a second database of address information stored remotely from said controller and accessible through said first network interface.

A 14. Apparatus comprising:
an image capture device which generates a digital record;
a printer interface which generates printed copy signals corresponding to the digital record, the printed copy signals being effective in printing an image derived from the captured image when coupled to a printer;
a controller which couples said image capture device and said printer interface, said controller having
a first network interface which connects to an area network for bidirectional exchange of digital data; and
a second network interface which connects to a second network for bidirectional exchange of digital data; and
a control program stored accessibly to and executable on said controller, said control program when executing enabling a user to select delivery of the digital record to each and all of said printer interface, said first network interface, and said second network interface.

15. Apparatus according to Claim 14 wherein said control program when executing on said controller enables a user to access a remotely stored database of address information.

16. Apparatus according to Claim 14 further comprising:
a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and enabling access to said database of address information stored in said memory.

A
17. Apparatus according to Claim 14 further comprising
a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and to selectively access one of said database of address information stored in said memory and a second database of address information stored remotely from said controller and accessible through said first network interface.

18. Apparatus comprising:
an image capture device which generates a digital record;
a printer which generates a printed copy derived from the digital record;
a controller which couples said image capture device and said printer, said controller having
a first network interface which connects to an area network for bidirectional exchange of digital data; and
a second network interface which connects to a second network for exchange of digital data; and

a control program stored accessibly to and executable on said controller, said control program when executing enabling a user to select delivery of the digital record to a selected one of said printer, said first network interface, and said second network interface.

19. Apparatus according to Claim 18 wherein said control program when executing on said controller enables a user to access a remotely stored database of address information.

20. Apparatus according to Claim 18 further comprising:

a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and enabling access to said database of address information stored in said memory.

21. Apparatus according to Claim 18 further comprising

a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and to selectively access one of said database of address information stored in said memory and a second database of address information stored remotely from said controller and accessible through said first network interface.

22. Apparatus comprising:

an image capture device which generates a digital record;
a printer which generates a printed copy derived from the digital record;
a controller which couples said image capture device and said printer, said controller having

a first network interface which connects to an area network for bidirectional exchange of digital data; and

a second network interface which connects to a second network for exchange of digital data; and

a control program stored accessibly to and executable on said controller, said control program when executing enabling a user to select delivery of the digital record to any selected two of said printer, said first network interface, and said second network interface.

23. Apparatus according to Claim 22 wherein said control program when executing on said controller enables a user to access a remotely stored database of address information.

24. Apparatus according to Claim 22 further comprising:
a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and enabling access to said database of address information stored in said memory.

520637 25. Apparatus according to Claim 22 further comprising
a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and to selectively access one of said database of address information stored in said memory and a second database of address information stored remotely from said controller and accessible through said first network interface.

26. Apparatus comprising:

an image capture device which generates a digital record;
a printer which generates a printed copy derived from the digital record;
a controller which couples said image capture device and said printer, said controller having

a first network interface which connects to an area network for bidirectional exchange of digital data; and

a second network interface which connects to a second network for exchange of digital data; and

A
1
a control program stored accessibly to and executable on said controller, said control program when executing enabling a user to select delivery of the digital record to each and all of said printer, said first network interface, and said second network interface.

27. Apparatus according to Claim 26 wherein said control program when executing on said controller enables a user to access a remotely stored database of address information.

28. Apparatus according to Claim 26 further comprising:

a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and enabling access to said database of address information stored in said memory.

29. Apparatus according to Claim 26 further comprising

a memory coupled to and housed with said controller;
said control program when executing on said controller further enabling a user to store a database of address information in said memory and to selectively access one of said database of address information stored in said memory and a second database of

address information stored remotely from said controller and accessible through said first network interface.

- A
30. A method comprising the steps of:
- capturing a digital record of a document;
 - executing on a controller a control program which enables a user to select delivery of the captured digital record to one of an associated printer, a first network interface, and a second network interface; and
 - performing in accordance to such selection one of:
 - 1. delivering the digital record to the printer to generate a copy of the document;
 - 2. delivering the digital record to the first network interface to generate an electronic mail message;
 - 3. delivering the digital record to the second network interface to generate a facsimile transmission to a remote facsimile receiver.

31. The method of claim 30 wherein the format of the electronic mail message is a format selected from the group consisting of PDF and Text.

32. A method comprising the steps of:
- capturing a digital record of a document;
 - executing on a controller a control program which enables a user to select delivery of the captured digital record to at least two of an associated printer, a first network interface, and a second network interface; and
 - performing in accordance to such selection at least two of:

- 1. delivering the digital record to the printer to generate a copy of the document;

2. delivering the digital record to the first network interface to generate an electronic mail message;
3. delivering the digital record to the second network interface to generate a facsimile transmission to a remote facsimile receiver.
33. The method of claim 32 wherein the format of the electronic mail message is a format selected from the group consisting of PDF and Text.
34. A program product comprising:
a computer readable medium;
a control program stored on said medium, said control program when executing on a controller which couples an image capture device, a printer, and first and second network interfaces, enabling a user to select delivery of a digital record captured by the device to one of the printer, the first network interface, and the second network interface by performing in accordance to such selection one of:
- (a) delivering the digital record to the printer to generate a copy of the document;
 - (b) delivering the digital record to the first network interface to generate an electronic mail message;
 - (c) delivering the digital record to the second network interface to generate a facsimile transmission to a remote facsimile receiver.
35. A program product comprising:
a computer readable medium;
a control program stored on said medium, said control program when executing on a controller which couples an image capture device, a printer, and first and second network interfaces, enabling a user to select delivery of a digital record captured by the